



# DAISY VP

DOSING PUMPS  
CONTROLLED BY OFIX VP



## A SCALABLE SOLUTION

Combining Daisy VP dosing pumps with an Ofix VP analyser, provides a real automatic water treatment device. It allows to control an automatic pH regulation as well as a chlorine dosing/regulating device.



## INTUITIVE APPLICATION

At a glance on your Vigipool application, view the essential parameters of your pool (pH, RedOx, T°C) and intelligently adapt your water treatment intelligently. The application allows you to access the data history and to control the treatment automatically.



## COMPACT ET UNIVERSEL

Daisy VP dosing pumps are available in two versions. Combine your Daisy pH or Daisy ORP dosing pump with the analyser for automatic pH control or to drive a chlorine dosing/regulating unit.



# MOVE FROM AN ANALYSER TO AUTOMATED PROCESSING



Combine Daisy VP dosing pumps with your connected analyser and turn your monitoring installation into a complete water treatment system



The two dosing pumps, wirelessly connected to your Ofix VP, use the information measured by the analyser to operate.



There are two spaces for the injectors directly in the Ofix VP, so there is no work to do on the pipe! Installation is simplified



**DAISY VP PH**  
Automatic pH control  
to be connected to 230V mains



**DAISY VP OX**  
Automatic RedOx control  
to be connected to 230V mains



# VIGIPOOL : THE TECHNICAL ROOM IN YOUR PHONE

Vigipool is your new smartphone application that allows you to always have your equipment room in your pocket. In this application, centralise the equipment in the technical room and control your devices connected to the house's Wifi from anywhere in the world. Vigipool allows you to access the various measurements of your Ofix VP and to have real time access to your equipment room.

### AN EVOLVING SOLUTION:

For an even more complete installation, add Vigipool-compatible devices to your technical room and see new functionalities added to your application (filtration control, LED spotlight control, etc.)



**REQUIRES A TREATMENT DEVICE**



**PROTECTED FROM THE ELEMENTS (RAIN, ALGAE)**



**DOES NOT INTERFERE IN THE POOL**

Reference	Model	Alim.	Injection volume max	Max. flow rate pump	Volume bassin max.	Conexion	Dimensions case
PF10J053	Daisy VP pH	230V AC	18 litres / day Adjustable	1.5 l/h	150 m <sup>3</sup>	Wifi at Ofix VP	130 x 115 x 35 mm
PF10J054	Daisy VP Ox						

Reference	Model	Alim.	pH meas.	RedOx meas.	Injector locations	Max pool vol.	Connection	Analyser dimensions	Installation	Probe
PF10J070	Ofix VP	230V AC	5 à 10 +/- 0.1	200 - 900 mV +/- 20mV	1 pH injector 1 chlorine injector	150 m <sup>3</sup>	Wi-Fi (local and remote) / Bluetooth®	185 x 120 x 50 mm	Ø50 mm	Platinum
PF10J071	Ofix VP Gold									Gold



Ne pas jeter sur la voie publique

ccei-pool.com